

Data Sheet

Customer:

Product: TO-220 Power Resistor – TR30 Series

Sizes.: 30W

Issued Date: 03-Jun-25

Edition: REV.C2



VIKING TECH CORPORATION
光頤科技股份有限公司
No.70, Guangfu N. Rd., Hukou
Township, Hsinchu County
303, Taiwan (R.O.C)

TEL:886-3-5972931
FAX:886-3-5972935•886-3-5973494
E-mail:sales@viking.com.tw

VIKING TECH CORPORATION KAOHSIUNG BRANCH
光頤科技股份有限公司高雄分公司
No.248-3, Sin-Sheng Rd., Cian-Jhen Dist., Kaohsiung,
806, Taiwan

TEL:886-7-8217999
FAX:886-7-8228229
E-mail:sales@viking.com.tw

VIKING ELECTRONICS (WUXI) CO., LTD.
光頤電子(無錫)有限公司
No.22 Xixia Road, Machinery & Industry Park,
National Hi-Tech Industrial Development Zone
of Wuxi, Wuxi, Jiangsu Province, China
Zip Code:214028
TEL:86-510-85203339
FAX:86-510-85203667•86-510-85203977
E-mail:china@viking.com.tw

Produced by (QC)	Checked (QC)	Approved by (QC)	Prepared by (Sales)	Accepted by (Customer)
03-Jun-25	03-Jun-25	03-Jun-25	03-Jun-25	
<i>Mandy Chang</i>	<i>Ben Chang</i>	<i>Ben Chang</i>		

TO-220 Power Resistor TO-220 Power Resistor

Features

- 30 watts at 25°C case temperature heat sink mounted
- TO-220 style power package
- Single screw mounting to heat sink
- Molded case for protection and easy to mount
- Electrically isolated case
- Non-Inductive design


Applications

- Gate Resistors in Power Supplies
- Snubbers
- Load and Dumping Resistors in CRT Monitors
- Automated Machine Controller
- Terminal Resistance in RF Power Amplifiers
- Voltage Regulation
- Low Energy Pulse Loading
- UPS




Two styles (no round holes and two small round holes) side by side.

Derating Curve




Derating Curve Slope : 0.24W/°K ;
Thermal resistance : 4.17°K/W

Construction



① Alumina Substrate	③ Lead
② Resistor Layer	④ Molding

Dimensions



Type	W (mm)	H (mm)	B (mm)	B1 (mm)	C (mm)	D (mm)	D1 (mm)	T (mm)	P (mm)	P1 (mm)	Weight (g) (1000pcs)	Packaging
												Tube
TR30	10.44 ±0.24	16.25 ±0.25	12.70 ±1.3	3.3 ±0.76	5.08 ±0.26	1.27 ±0.13	0.76 ±0.1	3.18 ±0.26	0.55 ±0.1	1.78 ±0.26	1155	50pcs

TO-220 Power Resistor

Part Numbering

TR	30	J	D	D	1001
Product Type	Power	Resistance Tolerance	Packaging Code	TCR (PPM/°C)	Resistance
	30: 30 Watts	D: ±0.5% F: ±1% J: ±5% K: ±10%	D: Tube	D: ±50 E: ±100 F: ±200 G: ±300 - : No Specified (±300~±700)	R100: 0.1Ω 0100: 10Ω 4700: 470Ω 1001: 1000Ω 1002: 10000Ω

Electrical Characteristics Specifications

Type	Item	Resistance Range				TCR (PPM/°C)
	±0.5%	±1%	±5%	±10%		
TR30	-	-	0.05Ω – 0.1Ω		No Specified (±300~±700)	
	-	≥ 0.1Ω - 1Ω			±300	
	-	≥ 1Ω - 5Ω			±100 ±200 ±300	
	≥ 10Ω - 100KΩ			±50 ±100 ±200		
	≥ 5Ω - 10Ω			±100 ±200 ±300		


- Operating Voltage: 420V max.
- Dielectric Strength: 1800VAC
- Insulation Resistance: 10GΩ min.
- Operating Temperature Range: -65°C to +150°C

Environmental Characteristics

Item	Requirement	Test Method
Temperature Coefficient of Resistance (T.C.R.)	As Spec.	Referenced to 25°C, ΔR taken at +105°C
Short Time Overload	ΔR±0.3%	2 times rated power with applied voltage not to exceed 1.5 times maximum continuous operating voltage for 5 seconds
Load Life	ΔR±1.0%	2,000 hours at rated power
Damp Heat with Load	ΔR±0.5%	40±2°C, 90~95% R.H., RCWV for 1000 hrs with 1.5 hrs "ON" and 0.5 hrs "OFF"
Solderability	90% min. coverage	245±5°C for 3 seconds
Thermal Shock	ΔR±0.3%	-65°C~150°C, 100 cycles
Terminal Strength	ΔR±0.2%	(Pull Test) 2.4N
Vibration, High Frequency	ΔR±0.2%	20g peak

- Lead Material: Tinned Copper
- Maximum Torque: 0.9 N·m
- When in Free Air at 25°C, the TR30 is Rated for 2.25W
- The Case Temperature is to be used for the Definition of the Applied Power Limit
- The Case Temperature Measurement must be made with a Thermocouple Contacting the Center of the Component mounted on the Designed Heat Sink.
- Thermal Grease should be Applied Properly.
- Storage Temperature: 25±5°C; Humidity <75%RH
- Shelf life: 1 years Max

■ Power Curve



REVISION HISTORY

<u>REVISION</u>	<u>DATE</u>	<u>CHANGE NOTIFICATION</u>	<u>DESCRIPTION</u>
Version C	Mar 31 ,2025		-Add Shelf life.
			-Modify product Dimensions
			-Modify the TCR specification for 0.05Ω – 0.1Ω from No Specified to No Specified (±300~±700)
			-Modify the TCR specification for ≥0.1Ω – 1Ω from No Specified to ±300
Version C1	May 14 ,2025		-Modify the operating voltage from 420V→350V.
			-Modify the operating temperature range from -65°C to +150°C → -55°C to +150°C.
			-Add Power Curve.
			-Add product image (two small round holes).
			-Modify the operating voltage from 350V→420V.
Version C2	Jun 03 ,2025		-Modify the operating temperature range from -55°C to +150°C → -65°C to +150°C